

VAS 741 081



PRODUCT DESCRIPTION

Electronic wheel balancer for passenger car with Touchscreen Monitor, mechanic locking system, sonar width measuring (for high volumes of wheel services shop).

The new design and the new GUI (Graphic user interface) allow high performances and accuracy with all type of cars, motorcycle and light trucks wheels.

SCOPE OF DELIVERY



WIDTH GAUGE



CLAMP FOR COUNTER-WEIGHTS



WEIGHT REMOVAL BLADE



GAUGE



RUBBER CUP



CALIBRATION PIN



FLANGE SUPPORT



METAL SHEET



AIRGO WHEEL LIFT

FEATURES

Product Features

FEATURES: VAS 741 081



NEW GRAPHIC USER INTERFACE

- New Digital display with high quality LCD technology, enhancing sharpness and brightness for a unique digital experience
- 22" Touch screen monitor with HQ graphic
- Just One touch selection
- Re-engineered and intuitive GUI



MULTI-FUNCTIONAL PEDAL

- Multifunctional: Electromechanical brake, Clamping, Unclamping
- Ergonomic design



NEW DESIGN

- More space available for tools and weights
- Everything at hand in an ergonomic design
- New, solid and no-slip weight tray



QUICK SELECTION PROGRAM (QSP)

Fast and Automatic recognition of
TOP3 Programs: Standard, Alu 2, Alu 3



2 INTERNAL LASER POINTERS

- One fixed laser 12 o' clock positioning for steel rims
- One auto-positioning laser for internal weight applications



1 LASER POINTER

- External
- Fixed positioning for steel rims

SELF DIAGNOSTIC

- Automatic check-up for easy troubleshooting
- Ready for remote access

AUTOMATIC TIRE POSITIONING

- Time saving for weight application

- Driven-auto positioning in the unbalancing position for internal and external weight application

OPTIMIZED STATIC AND DYNAMIC FUNCTION (OSD)

The new wheel balancer suggests the correct tire's position to guarantee the best matching between the rim and the wheel

PRINT OUT

- Detailed balancing procedure report

SOFTWARE LANGUAGES – MONITOR MODEL:

Italian, French, English, German, Spanish, Portuguese, Czech, Polish, Hungarian, Slovenian, Dutch, Serbian, Finnish, Turkish, Croatian, Swedish, Lithuanian, Russian, Israeli, Bulgarian, Slovak, Danish, Persian, Japanese, Icelandic, Chinese and Korean

- Internal arm
- Sonar for width measurement

TECHNICAL DATA

Technical Data

Power supply	230 V 1 ph 50/60 Hz
Balancing speed (50 – 60 Hz)	220 rpm \pm 2%
Max wheel weight	80 Kg
Max wheel diameter	1150 mm
Max wheel width	508 mm
Rim diameter	13"-30" / 12"-40"
Rim width	3"-15" / 3"-20"
Accuracy	5% \pm 1g/1g
Measuring time	5s